


Specification

Basic series

BH5470




BH5470




Features

- Innovative buckle plug, no light leakage
- Carrier tight fit design carrier buckle extremely convenient for installation and maintenance
- Designed in anti-leaky block piece, perfect details
- Free to collocation ordinary PC diffuser, flexible diffuser, anti-glare flexible diffuser, black diffuser, aluminum diffuser
- Provide standard extenders, customizable interconnected corners
- Built-in linear power supply, invisible and beautiful
- Various installation ways: pendant, recessed, surface



Details




Standard Configuration

Picture	Item	Parameter
	①Profile /②Carrier:	Profile weight: 4.02kg/2.5m Size: L2500*W54*H70mm Material: AL6063-T5 Surface processing: Anodizing
	④Cover	Type: Frosted diffuser Material: PC ; Light transmittance: 75% Size: L2500*W48.8*H5.6mm PC Feature: The diffuser will extend (shrink) 0.8mm/m when the temperature raises (drops) 10°C.
	⑤Cover(up ward)	Type: Frosted diffuser Material: PC ; Light transmittance: 75% Size: L2500*W48.8*H5.6mm PC Feature: The diffuser will extend (shrink) 0.8mm/m when the temperature raises (drops) 10°C.
	④End cap	Model: EC-BS5470FSS Size: L54*W70*H10.5mm
	⑥Install screw	Model: CL-01 Size: M3.5*40mm
	⑦Cable clip	Model: BG-02

Optional Accessories

Picture	Item	Parameter
	⑧Flexible strip DL8280-24V-18mm (lighting downward)	Material: FPC,CCT:2700/3000/3500/4000/5000/6500K; CRI > 80/>90; Voltage: 24V; Power: 25W/m; Lumen: 3400Lm/m; Width: 18mm; Minimum cutting unit: 14LEDs/50mm;
	⑨Flexible strip DL8160-24V-8mm (lighting upward)	Material: FPC, CCT : 2700/3000/3500/4000/5000/6500K; CRI > 80/>90; Voltage: 24V; Power: 15W/m; Lumen: 2150Lm/m; Width: 8mm; Minimum cutting unit: 8LEDs/50mm;
	⑩Pendant cable with junction box	Model: PY-DXXX Junction box L80*W80*H30mm
	⑩Pendant cable without junction box	Model: PN-DXX Steel cable D1.5*2000/4000mm
	Surface mounted buckle	Model: CL-06 Size: L90.5*W54*H5.9mm
	⑪clip	Model: CP-16
	Pendant rod	Model: PG-IA2 Size: 1-2m
	Reflective paper	Model: BG-13 Size: L15000*W19*H0.188mm
	Integrated track cabling accessories	Dimming: CM-03; CM-06 No dimming: CM-04; CM-05
	⑫Power supply	Model: BN-V24-060P-V1 Size: L329*W30*H17mm
	Whole lamp splice	Model: EX-24 Size: L80*W51*H6mm

Cover type

Picture	Item	Parameter
	②cover	Type: Diffuse flexible mask Material: PC + silica gel Transparency: 70 % Size: L50000*W48.8*H5.6mm
	②cover	Type: Aluminum mask Material: Aluminum alloy Size: L2500*W48.8*H5.6mm
	②cover	Type: Night mask Material: PC Transparency: 15 % Size: L2500*W48.8*H5.6mm

Corners

L-type corner (L90- BH5470)



Al6063-T5
L150*W150*H70mm

T-type corner(T90- BH5470)



Al6063-T5
L300*W177*H70mm

X-type corner(X90-BH5470)





Al6063-T5
L300*W300*H70mm

* The corners without light source.


Optical Parameter

DL8280-24V-18mm/DL8160-24V-8mm light source, frosted diffuser




Package

COLORS Individual :



COLORS Whole :



Components	Packaging material	Size(mm)	NW(kg)	GW(kg)	Content
Single piece	Hat box	2560*99*65mm	4.62	5.12	1pcs/box
COLORS Individual	Hat box	2580*228*219mm	27.72	30.72	6pcs/box
COLORS Whole	Paper box	2580*192*168mm	27.72	30.72	6pcs/box